



Rated power: **7 - 80W**
 Rated voltage PRI: **230V 50/60Hz**
 Rated voltage SEC: **12; 24V DC**

New generation electronic pulse power supplies are designed especially for powering LED and halogen lighting systems in various forms (strips, modules, etc.). Load range from 0,5W to rated power. Protection against short circuit and/or overload. The transformers are made with Class II insulation and protection grade IP20, maximum ambient temperature 40°C. Manufactured in compliance with IEC61347, EN55015, EN61000, EN61547.

| Type | Power | Current for Usek | Dimensions [mm] | | | Weight [kg] |
|--------------|-------|------------------|-----------------|----|------|-------------|
| | [W] | [A] | A | B | C | |
| ZLD 07-12 LF | 7 | 0,58 | 86 | 35 | 21,5 | 0,05 |
| ZLD 12-12 LF | 12 | 1,00 | 106 | 43 | 23 | 0,08 |
| ZLD 16-12 LF | 16 | 1,33 | 106 | 43 | 23 | 0,08 |
| ZLD 24-12 LF | 24 | 2,00 | 140 | 47 | 25 | 0,13 |
| ZLD 33-12 LF | 33 | 2,75 | 140 | 47 | 24 | 0,14 |
| ZLD 54-12 LF | 54 | 4,50 | 152 | 59 | 32 | 0,27 |
| ZLD 65-12 LF | 65 | 5,40 | 152 | 59 | 32 | 0,29 |
| ZLD 80-12 LF | 80 | 6,67 | 157 | 63 | 35 | 0,34 |

| Type | Power | Current for Usek | Dimensions [mm] | | | Weight [kg] |
|--------------|-------|------------------|-----------------|----|------|-------------|
| | [W] | [A] | A | B | C | |
| ZLD 07-24 LF | 7 | 0,29 | 86 | 35 | 21,5 | 0,05 |
| ZLD 12-24 LF | 12 | 0,50 | 106 | 43 | 23 | 0,08 |
| ZLD 16-24 LF | 16 | 0,67 | 106 | 43 | 23 | 0,08 |
| ZLD 24-24 LF | 24 | 1,00 | 140 | 47 | 25 | 0,13 |
| ZLD 33-24 LF | 33 | 1,38 | 140 | 47 | 24 | 0,14 |
| ZLD 54-24 LF | 54 | 2,25 | 152 | 59 | 32 | 0,27 |
| ZLD 65-24 LF | 65 | 2,70 | 152 | 59 | 32 | 0,29 |
| ZLD 80-24 LF | 80 | 3,33 | 157 | 63 | 35 | 0,34 |